







## FREESTANDING BLOODBANK GLASS DOOR (432x250ml bags)







- **Innovative Controller with LCD Display** Fully meets MHRA guidelines
- Heart Temperature Monitoring Software  $\checkmark$ Records air and load temperatures constantly, holding a full 7 day alarm history
- +2°C to +6°C Load Temperature (bag temp) Range
  - **USB Slot Control Panel** A USB stick can be plugged into control panel, allowing user to download temperature information as often as required
- $\checkmark$ **Internal LED Light**
- **Lockable Castors** for ease of movement
  - **Self Closing Door** Doors will close when positioned anything less than 90° open, and self lock for maximum security
- **Auto Defrost Feature**

### ✓ **Fully Removable, Vented Drawers** Easy-to-use drawer system offers maximum durability and allows cool air to follow correct path inside unit

**Easy Clean Interior** 

444440363 BBK432G Freestanding Bloodbank Glass Door (432x250ml k	l bags)

 $\checkmark$ 

**Glen Dimplex Professional Appliances** Stoney Lane, Prescot, Merseyside, L35 2XW

Tel: 0844 815 3755 Email: info@gdpa.co.uk

# MEDICAL

### www.lec-medical.co.uk







### FULL SPECIFICATION – BBK432G FREESTANDING BLOODBANK GLASS DOOR (432x250ml bags)

Description	Freestanding
SKU Code	44440363
GDPA Code	BBK432G
No. of blood bags (250ml fill)	432
No. of blood bags (450ml fill)	216
Capacity (litres)	439
Working Temperature	+4°C
Load Temperature (bag temp)	+2°C to +6°C
Door	Single
Door Type	Glass
Door Construction	Double Glazed
Self Closing Door	Yes
Unit External Width (mm)	680
Unit External Depth (mm)	850
Unit External Height (mm)	1980
Product Weight (kg)	259
Packed Width (mm)	TBC
Packed Depth (mm)	TBC
Packed Height (mm)	TBC
Packed Weight (kg)	279
Internal Dimensions (mm) (WxDxH)	560 x 640 x 1225
No. of Drawers	6
Lock Type	Digital (with 2 key fobs)
Digital display (LCD)	Yes
Internal Light (LED)	Yes
Core Temperature (audible/digital)	Yes
Air Temperature Alarm	Yes
Door Open Alarm	Yes
Mains Failure Alarm	Yes
Remote Alarm contacts	Yes
Fan Fail Alarm	Yes
Back-up Battery Alarm (visible)	Yes
Compressor Battery Back-up	Yes
Load, Air & Defrost Sensor Fail Alarm	Yes
Controller Battery Back-up	Yes
USB	Yes
Chart Recorder	Yes
Ambient working Temperature	
Castors	Yes (4, 2 lockable at front)
Adjustable Feet	-
Fixed Feet	-
Fan Type	Axial
Automatic Defrost	Yes
Dual Refrigeration	Yes
Refrigerant	R134a
Medical Devices Certification	Yes
BS4376 Compliant	Yes
Voltage	220v-240v 50Hz/60Hz