



UNDER-COUNTER BLOODBANK GLASS DOOR (48x250ml bags)



- ✓ **Innovative Controller with LCD Display**
Fully meets MHRA guidelines
- ✓ **Heart Temperature Monitoring Software**
Records air and load temperatures constantly, holding a full 7 day alarm history
- ✓ **+2°C to +6°C Load Temperature (bag temp) Range**
- ✓ **USB Slot Control Panel**
A USB stick can be plugged into control panel, allowing user to download temperature information as often as required
- ✓ **Internal LED Light**
- ✓ **Lockable Castors**
for ease of movement
- ✓ **Self Closing Door**
Doors will close when positioned anything less than 90° open, and self lock for maximum security
- ✓ **Auto Defrost Feature**
- ✓ **Fully Removable, Vented Drawers**
Easy-to-use drawer system offers maximum durability and allows cool air to follow correct path inside unit
- ✓ **Easy Clean Interior**

SKU CODE:

PRODUCT CODE:

DESCRIPTION:

444440881

BBK48GUC

Under-counter Bloodbank Glass Door (48x250ml bags)



FULL SPECIFICATION - BBK48GUC UNDER-COUNTER BLOODBANK GLASS DOOR (48x250ml bags)

Description	Under-counter
SKU Code	444440881
GDPA Code	BBK48GUC
No. of blood bags (250ml fill)	48
No. of blood bags (450ml fill)	30
Capacity (litres)	78
Working Temperature	+4°C
Load Temperature (bag temp)	+2°C to +6°C
Door	Single
Door Type	Glass
Door Construction	Double Glazed
Self Closing Door	Yes
Unit External Width (mm)	520
Unit External Depth (mm)	645 (includes handle depth of 45mm)
Unit External Height (mm)	830
Product Weight (kg)	72.5
Packed Width (mm)	570
Packed Depth (mm)	640
Packed Height (mm)	940
Packed Weight (kg)	79
Internal Dimensions (mm) (WxDxH)	420 x 440 x 352
No. of Drawers	2
Lock Type	Digital (with 2 key fobs)
Digital display (LCD)	Yes
Internal Light (LED)	Yes
Core Temperature (audible/digital)	Yes
Air Temperature Alarm	Yes
Door Open Alarm	Yes
Mains Failure Alarm	Yes
Remote Alarm contacts	Yes
Fan Fail Alarm	Yes
Back-up Battery Alarm (visible)	Yes
Compressor Battery Back-up	Yes
Load, Air & Defrost Sensor Fail Alarm	Yes
Controller Battery Back-up	Yes
USB	Yes
Chart Recorder	Yes
Ambient working Temperature	Max: +38°C, Min: +10°C
Castors	Yes (4, 2 lockable at front)
Adjustable Feet	-
Fixed Feet	-
Fan Type	Tangential
Automatic Defrost	Yes
Dual Refrigeration	No
Refrigerant	R600a
Medical Devices Certification	Yes
BS4376 Compliant	Yes
Voltage	220v-240v 50Hz/60Hz