



FREESTANDING LABORATORY FRIDGE SOLID DOOR 288L WHITE



- ✓ **+2°C to +10°C Operating Temperature Range**
Desired temperature can be set by the user
- ✓ **NEW Advanced Controller**
Records temperatures accurate to 0.1°C
- ✓ **NEW Unique Anti Microbial Handle**
Helps prevent the growth of bacteria and minimise the potential for cross contamination
- ✓ **Fitted Lock as Standard**
Maintains security and ensures the unit can only be accessed by approved personnel
- ✓ **Fitted Rollers**
For ease of movement
- ✓ **Wire Shelves**
Enables optimum air flow inside unit
- ✓ **Audible Warning Alarms**
Alerts user should internal temperature deviate from set parameters

SKU CODE: **PRODUCT CODE:**

444440966 LSR288UK

DESCRIPTION:

Freestanding Laboratory Fridge Solid Door 288L White



FULL SPECIFICATION – LSR288UK FREESTANDING LABORATORY FRIDGE SOLID DOOR 288L WHITE

Description	Freestanding
SKU Code	444440966
EAN Code	5052263009660
GDPA Code	LSR288UK
Gross Capacity (L)	288
Net Capacity (L)	284
Unit External Width (mm)	595
Unit External Depth (mm)	634
Unit External Height (mm)	1570
Product Weight (kg)	58
Packed Width (mm)	657
Packed Depth (mm)	734
Packed Height (mm)	1585
Packed Weight (kg)	63
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	480 x 445 x 1382 (step: 175d x 255h)
External Finish	White
Internal Finish	White
Type of Plastic	SRL800 (HIPS/ABS Mix)
Temperature Range	+2°C to +10°C
Colour	White/Green
Door Type	Solid
Door Style	Hinged, Reversible
Door Open Depth (mm)	1185
Replacement Door Seal	No
Open Door Sensor	Yes
Lock	Yes
Adjustable Feet	2 Adjustable Feet, 2 Rear Rollers
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Number of Shelves	5
Number of Shelf Positions	12
Shelf Size	5: 340 x 497 x 6
Shelf Material	Wire
Moulded Drawers	1 Solid
Adjustable Door Bins	4 Solid
Interior Light	No
Fan	No
Spark Free	Yes
Auto or Manual defrost	Automatic
Controller type	Digital, External
Climate Class	SN
Refrigerant Type	R600a
CFC Free	Yes
HFC Free	Yes
HCFC Free	Yes
UK 3 Pin Plug	Yes
Other Plug Types Available	Yes
Voltage Supply	230
Aux Output	No
Insulation Thickness (mm)	60
Insulation Type	Cyclopentane
Anti Microbial Handle	Yes